

OSHA Safety Sign Standards Update

SHA Signs

With OSHA's regulatory update for workplace safety signs, organizations can either use their current OSHA signage which follows the American National Standard Institute (ANSI Z53 and Z35 1967-1968 standards), or new signage that incorporates the latest ANSI Z535 standard (2013).

OSHA adopted the new ANSI standard to better communicate safety messages in the workplace. The recommended new visual signage depicts updated headers, greater use of symbols and in some instances, consequence and avoidance statements.

This new line of facility safety signs gives organizations the opportunity to elevate safety communications in their operations. Organizations will increasingly adopt the new sign formats which will eventually replace the previous standard OSHA signage used for many years.

CAUTION
SLIPPERY
WHEN WET

Safety Alert Symbol

A CAUTION

Slippery
when wet
Serious injury
may occur

Use of Symbol

CAUTION Signs

Pack: 5; Sugg. Retail: \$3.29



be kept closed







5501



A CAUTION
Slippery
when wet
Serious injury
may occur



5590

5620

5661

5670



60 Meadow Lane, Northfield, OH 44067

www.hy-ko.com

Signs Update





5400

5410

NOTICE Signs

Pack: 5; Sugg. Retail: \$3.29







5800

SAFETY FIRST Signs

Pack: 5; Sugg. Retail: \$3.29

SAFETY FIRST

Do not enter unless wearing safety equipment







5710

5720

5140

5321

5810

5730

Pack: 5; Sugg. Retail: \$3.29

DANGER Signs










5010



5081











5201

5121







5230

5351



